LINIAR - Modlok Bi-fold Doors

Document Q required - tick here []

ORDER FROM:	REFERENCE:		REQUIRED):	
DELIVERY ADDRESS (IF REQD)					
Maximum sash size 1000mm x 2150mm	Clearly mark on the grid shown the configuration required. The elevation of the door is as viewed from the				
Maximum overall width 4500mm	outside. Mark along the arrows the direction that each panel has to travel.			Right Jamb	
please refer to our full range of profile colours on the adjacent page	If you have 2 swing panels, indicate on this drawing which panel you would like to open first (with "FIRST")			Righ	
Colour Outside Glazed / Unglazed					
Colour Inside		Glass Type / Obscured Patten			
Smooth / Woodgrain - if applicable		Georgian, lead etc.			
Bead type		Glass spacer bar type/colour			
Width (including extensions)					
Height (including extensions)					
Threshold Type					
Cill size					
Drainage required					
Opens In or Out					
Internal D handle colour White	e[] Gold [] Black [] Chrome]			
Main handle colour White	e[] Gold[] Black[] Chrome] Satin Silver [] Bright Bronze []	Satin Bronze []	
Cylinder type					

Liniar Bi-Fold Colour Options in Sculptured Frame		Chamfered Bead	Ovolo Bead
Smooth finish inside and out			
White	RAL: 9003	•	•
Cream	RAL: 1015		•
Woodgrain with smooth white on inside			
Rosewood	No RAL number available	•	•
Golden Oak	RAL: 8001	•	•
Black	RAL: 8022		•
Chartwell Green	No RAL number available		•
Cream	RAL: 9001		•
Grey	RAL: 7016	•	•
Woodgrain inside and out			
Cream	RAL: 9001		•
Rosewood	No RAL number available	•	•
Golden Oak	RAL: 8001	•	•
White Ash	RAL: 9010		•
Irish Oak	No RAL number available		•

Liniar Bi-Fold Colour Options in Chamfered frame		Chamfered Bead	Ovolo Bead
Woodgrain inside and out			
Grey	RAL: 7016	•	•