Prestige Lift & Slide Patio survey sheet

Garrard Windows Ltd, 1-3 Harvington Park, Pitstone, LU7 9GX | 01296 668899

Inner out out Out Order Order Order Order Out Out Out Out Order Order Order Order Out	DIMENSIONS Max 6000 (w) x 2600mm (h)					restige
Prestige Patio please fill in this form and email back to aluminium@garrardwindows.co.uk	Width (mm) Height (mm) including cill if required					LIFT & SLIDE PATIO DOOR
Threshold Low Threshold with Ramp 'Instavaliable or triple gads. Standard Frame Standard Frame with Nose Standard Frame Colour Ext Int Pure White 9010 Matt Glazing units you will use glazing units you wi			Door Inner	g	Prestige Patio please fill in this form and email back to aluminium@garrardwindows.co.uk	
Contract email Delivery address for these items			r	Conte	mporary	Name
Standard Frame		not available	_	_		
Sash and Frame Colour Ext Int	on triple track Standard Frame			36mm TG 1.1 U-value 44mm TG 1.0 U-value Contemporary only		
Pure White 9010 Matt	Sash and Frame Colour	Ext In	it			
Anthracite Crey 7016 Matt]	glazing units you will use Figures are whole door U-values bas	sed on	
Standard 80mm]	, and the second second		Preferred delivery date
Agate Grey 7038 Matt Squirrel Grey 7000 Matt Pastel Turquoise 6034 Matt Chocolate Brown 8017 Matt Silver Metallic Effect Mid Bronze Metallic Effect Black Metallic Effect Black Metallic Effect Buject to minimum order qty. Price on application Top Left Right When viewed from outside) Options Trickle Vents 25mm frame extension required. 2 x vents split equally as standard Main Handle Finish Your details Name Company Contact number Contact email Address External with 50/10 cyclinder Upgrades (8cth can be fitted if required and are recommended for extra large door soathes over 200kg / 300kg Drop Assist¹ Lift Assist² Signature Notes	Jet Black 9005 Matt		<u> </u> 	Standard 80mm		Notes
Squirrel Grey 7000 Matt	Agate Grey 7038 Matt]			
Matt Silver Metallic Effect Mid Bronze Metallic Effect Black Metallic Effect Bespoke Subject to minimum order qty. Price on application Top Left Right When viewed from outside) Options Trickle Vents 25mm frame extension required. 2 x vents split equally as standard Door Hardware Handle Internal with Finger Grip External. Standard with 50/10 cylinder Handle Internal and External with 50/50 cyclinder Upgrades (Soth can be fitted if required and are recommended for extra large door sashes over 200kg //300kg Drop Assist¹ Lift Assist² Signature Notes	Pastel Turquoise 6034]	Handle options:		Your details
Bespoke Subject to minimum order qty. Price on application Top Left Right (When viewed from outside) Drop Assist¹ Lift Assist² Signature Notes Trickle Vents 25mm frame extension required. 2 x vents split equally as standard Address Signature Address Address Signature	Matt Silver Metallic Effect] 	Handle Internal with Finger Grip External- Standard with 50/10		Company
Frame Extensions (When viewed from outside) 25mm Drop Assist¹	Bespoke Subject to minimum order qty.]	Handle Internal and External with 50/50		
Options Trickle Vents 25mm frame extension required. 2 x vents split equally as standard Notes	Frame Extensions (When viewed from outside)		Right	(Both can be fitted if required and are re for extra large door sashes over '200kg / 200pg Assist1	² 300kg	
	Trickle Vents 25mm frame extension required. 2 x vents split of		Notes	<u></u>	Signature	






1. Low Threshold with Ramp (25mm high) tested to the requirements of Part M *Only available in double track

2. Standard Outer Frame (38mm high inside)

3. Standard Outer Frame with Clip-on Cill Nose (38mm high)

Threshold Options

1. Low Threshold with Ramp





Square cut frames for easy assembly on site if required


restige IFT & SLIDE PATIO DOO

At a glance

- Double and Triple Track Options
- Max 6.5 x 2.5m
- Max 400kg Sash
- Slim 106mm Frame to Sash Sightline
- Standard 80mm
 Interlock Sightline
- Ultra Slim 52mm Interlock Option
 Suitable for most twin track doors
- Up to 44mm Triple Glazing


36mm on stepped sashes

2. Standard Outer Frame





Concealed buffers help dampen sash operation





Flush jambs prevent snagging and keep visual lines clean