## Prestige Lift & Slide Patio survey sheet

Garrard Windows Ltd, 1-3 Harvington Park, Pitstone, LU7 9GX | 01296 668899

Dimensions Max 6500 (W) x 2600mm (h)					Trestige
Width (mm)	Height (mm) including cill if required				LIFT & SLIDE PATIO DOOR
Configuration (When viewed from outside)			Sliding Door Inner		To order or request a quote for a Prestige Patio please fill in this form and email back to aluminium@garrardwindows.co.uk  QUOTE
Sash style Contemporary Stepped				ontemporary	Job details  Name  Reference
Threshold		Glazing		Contact number	
<b>Low Threshold with Ramp</b> *not available on triple track			<b>28mm DG</b> 1.4 U-value <b>36mm TG</b> 1.1 U-value		Contact email
Standard Frame			<b>44mm TG</b> 1.0 U-value		Delivery address for these items
Standard Frame with Nose		Contemporary only  Laminated			
Sash and Frame Colour	Ext	Int	Unglazed Still tick whi		
Pure White 9010 Matt			glazing units you will use	· _	
Hipca Gloss White 9910			Part L standard configurations		Preferred delivery date
Anthracite Grey 7016 Matt			Slim Interlock Option		Notes
Jet Black 9005 Matt  Cream 9001 Matt			Slim 52mm		
Agate Grey 7038 Matt			*Not available on 3 Pane option		
Squirrel Grey 7000 Matt			Main Handle Finish		
Pastel Turquoise 6034			Handle options:		Your details
Matt		White, Black, Silver			
Chocolate Brown 8017 Matt			Door Hardware		Name Company
Silver Metallic Effect			Handle Internal with Finger Grip External		Contact number
Mid Bronze Metallic Effect			Standard with 50/10 cylinder		Contact email
Black Metallic Effect			Handle Internal and		Address
Bespoke Subject to minimum order qty.			<b>External</b> with 50/50 cyclinder		-
Price on application			Upgrades		
Frame Extensions	Top Le	ft Right	(Both can be fitted if required and for extra large door sashes over 12		
(When viewed from outside)  25mm			Drop Assist <sup>1</sup>		
			Lift Assist <sup>2</sup>		Signature
Options Notes					
Trickle Vents 25mm frame extension required. 2 x vents split equally as standard					
Head Drip					
			1		






 Low Threshold with Ramp (25mm high) tested to the requirements of Part M
 \*Only available in double track


**2. Standard Outer Frame** (38mm high inside)

**3. Standard Outer Frame** with Clip-on Cill Nose (38mm high)

## Threshold Options

## 1. Low Threshold with Ramp






Square cut frames for easy assembly on site if required




- Double and Triple Track Options
- Max 6.5 x 2.5m
- Max 400kg Sash
- Slim 106mm Frame to Sash Sightline
- Standard 80mm
   Interlock Sightline
- Ultra Slim 52mm
   Interlock Option
   Suitable for most twin track doors
- Up to 44mm Triple Glazing


36mm on stepped sashes

## 2. Standard Outer Frame





Concealed buffers help dampen sash operation





Flush jambs prevent snagging and keep visual lines clean