VISOFOLD 6000 Aluminium Bi-fold Doors

Please tick: Order [] Quote []
New Build [] Replacement/Extension [] Doc Q compliant []

Company Name: Address: Postcode: OPENING CONFIGURATION Tel: Fax: Inward [] Outward []	
Tel: Fax: Inward [] Outward []	
D.P Aller	
Delivery Address:	
DELIVERY OPTION	
Postcode: Fully assembled []	
Kit form (must be if over 5100mm) []	
SINGLE COLOUR Glazed (full spec inc spacer bar colour) []	
White [] Unglazed []	
RAL No.:	
DUAL COLOUR SASH OPTION (see overleaf for details)	
Internal RAL No.: External RAL No.: Standard []	
Heritage type (dummy transom available) []	
FRAME SIZES	
Width (mm) BOTTOM TRACK DETAIL (see overleaf for details)	
Height (mm) Standard outer frame 55mm []	
Note: You <u>must</u> allow 10mm tolerance between frame and opening size 175mm Integrated cill/threshold []	
17.511111 Integrated only the establish	
CILL Included in overall frame height (cill height is 25mm) DRAINAGE REQUIRED	
150mm [] 16mm Drainage tray [] Concealed []	
190mm [] No cill (only if internal door) [] None (only if internal door) []	
250mm [] — Ho om (om) minternal door) []	
HINGE COLOUR (inc. D-HANDLE) MAIN HANDLE COLOUR	
White [] Colour Matched [] White [] Black [] Chrome []	
Black [] Black (with chrome D) [] Gold [] Satin Silver [] Colour Matched [1
Brushed Silver L/L (Hoppe) []	•
HEAD PACKER Brushed Silver separate handle & escutcheon VBH []	
42mm []	
Included in height [] SHOOTBOLT HANDLE	
Standard []	
TRICKLE VENTS (in 42mm head packer) Flush [] (must be flush if you have an even amount of doors	
Yes [] Please draw position on grid all sliding one way - outside access not available)	
Quantity 1 [] 2 [] 3 []	
SHOOTBOLT HANDLE COLOUR	
MAGNETIC PANEL CATCH White [] Black [] Chrome []	
Chrome [] Colour Matched [] Brushed Silver [] Colour Matched [] Gold []	
	_
Clearly mark on the grid shown the	
configuration required. The elevation of the	
door is as viewed from the outside. Mark	i e
along the arrows the direction that each panel	Jan
along the arrows the direction that each panel has to travel.	. — — — — Right Jamb
의 기계	ļ iš
drawing which panel you would like to open	
first (with "FIRST")	İ

Maximum sash size 1000mm x 2200mm Minimum recommended sash size 700mm x 1775mm

